



## SPECIFICATION SUMMARY

# Han Van Collection Elite 5.5mm

# SPEC Living

modern. flooring. solutions.

### PRODUCT

Product Type:	Rigid Core Stone Polymer Composite
Overall Thickness:	5.5mm (4mm + 1.5mm)
Wear Layer:	20 Mil (0.5mm)
Finish:	Spectanium™ Ceramic Bead with Nanosilver
Embossing:	Deep Embossed
Size:	7" x 48" Standard
Packing:	24.29 sf/Carton, 50 Cartons/Pallet, 20 Pallets/20'
Lbs Carton:	55 Lbs
Install Method:	Float
Attached Pad:	1.5mm Eiso™ PEVA pad

### PERFORMANCE

#### Commercial Grade Rigid Core Plank

Classification	ASTM F3261 - Class I, Type B, Grade 1, Class B ASTM F 3261	
Thickness	ASTM F 387 Nominal ± 0.008 in.	Pass
Wear Layer	ASTM F 410	Pass
Size	ASTM F 2055 ±0.016 in. per linear foot	Pass
Squareness	ASTM F 2055 0.010 in. max	Pass
Residual Indentation	ASTM F 1914 <.007	Pass
Dimensional Stability	ASTM F 2199 0.020% per linear foot	Pass
Chemical Resistance	ASTM F 925 No Change	Pass
Resistance to Heat	ASTM F 1514 ΔE ≤ 8	Pass
Resistance to Light	ASTM F 1515 ΔE ≤ 8	Pass
Static Load	ASTM F970 Residual Indentation less than or equal to 0.005	Pass
Flame Spread	ASTM E 648 0.45 watt/cm2 or more Class I	Pass
Smoke Density	ASTM E 662 ≤ 450 v	Pass
Warranty	30 Year Residential / 10 Year Commercial	

### SUPPLEMENTARY

Formaldehyde	ASTM D6007	Carb II Compliant
Heavy Metals Content	ASTM F963	Pass
Indoor Sound Transmission IIC	ASTM E492/E989	66
Sound Transmission Class	ASTM E90/E413	68

For warranties, certifications, installation and maintenance instructions please contact your SPEC Living sales representative or visit our website [www.specliving.com](http://www.specliving.com)



by SCS Certified

**CONTACT**

445 Hamilton Avenue  
White Plains NY 10601  
MAIN 914.220.8195  
SALES 914.220.8195  
info@specliving.com