



SPEC Living

modern. flooring. solutions.

CATEGORY

Advanced Laminate Flooring

Thickness:	12mm (10mm Core + 2mm Sound Isolation Layer)		
Width:	7.7"		
Length:	60"		
Packing:	25.436 SF Carton, 60 Cartons Pallet, 20 Pallets Per 40'		
Underlayment:	2mm HD Eiso™ Sound Isolation Layer		
Edge:	U Groove / Square Edge		
Wear Layer:	45 gram Spectanium™ Embedded Finish Technology		
Embossing:	EIR		
Locking System:	Uniclic		
Core:	Triton WP-501 (500+ Hour Waterproof)		
Installation Grade:	Above, On, Below		
Warranty:	Lifetime residential / Lifetime Structural / 10 Year Light Commercial		
Tests:	Formaldehyde:	ASTM D6007-14	Result = Carb II & TSCA Title VI Compliant
	Critical radiant Flux:	ASTM E648-19a	Result = Meets or exceeds class I
	Dimensional Stability:	ASTM F2199-18	Result = Pass
	Coefficient of Friction:	ASTM D2394-2017	Result = MD Sliding Mean 0.41 Dry / 0.57 Wet
	Large Ball Impact Resistance:	NALFA 3.5	Result = Class 4 Heavy Commercial
	Small Ball Impact Resistance:	NALFA 3.6	Result = Class 4 Heavy Commercial
	Locking Strength:	ISO 24334-2014	Result = Pass Fmax(N) LSJ 1403 / SSI 1043
	Scratch Resistance:	ISO 1518-1-2019	Result = Pass Horizontal & Vertical @ 20(N)
	Thickness Swell:	NALFA 3.2	Result = Class 4 Heavy Commercial
	Wear Resistance:	NALFA 3.7	Result = Class 3+ Commercial
	Stain Resistance:	NALFA 3.4	Result = Class 4 Heavy Commercial
	Light Resistance:	NALFA 3.3	Result = Class 4 Heavy Commercial
	Castor Chair:	NALFA 3.9	Result = Class 4 35,000 Cycles No Effect
	Surface Bonding:	NALFA 3.10	Result = Class 4 1.5 N/mm2

Certifications:

