



SPECIFICATION SUMMARY

Han Van Collection 5mm

SPEC Living
Multi Family Flooring Experts

PRODUCT

Product Type:	Rigid Core Stone Polymer Composite
Overall Thickness:	5mm (4mm + 1mm)
Wear Layer:	20 Mil (0.5mm)
Finish:	Spectanium™ Ceramic Bead with Nanosilver
Embossing:	Real wood deep embossing pattern
Size:	7" x 48" Standard
Packing:	24.16 sf/Carton, 65 Cartons/Pallet
Lbs Carton:	55 Lbs
Install Method:	Float
Attached Pad:	1mm Eiso™ sound reducing IXPE pad - attached

PERFORMANCE

Commercial Grade Rigid Core Plank

Classification	ASTM F3261 - Class I, Type B, Grade 1, Class B ASTM F 3261	
Thickness	ASTM F 387 Nominal ± 0.008 in.	Pass
Wear Layer	ASTM F 410	Pass
Size	ASTM F 2055 ±0.016 in. per linear foot	Pass
Squareness	ASTM F 2055 0.010 in. max	Pass
Residual Indentation	ASTM F 1914 <.007	Pass
Dimensional Stability	ASTM F 2199 0.020% per linear foot	Pass
Chemical Resistance	ASTM F 925 No Change	Pass
Resistance to Heat	ASTM F 1514 ΔE ≤ 8	Pass
Resistance to Light	ASTM F 1515 ΔE ≤ 8	Pass
Static Load	ASTM F970 Residual Indentation less than or equal to 0.005	Pass
Flame Spread	ASTM E 648 0.45 watt/cm2 or more Class I	Pass
Smoke Density	ASTM E 662 ≤ 450 v	Pass
Warranty	30 Year Residential / 10 Year Commercial	

SUPPLEMENTARY

Formaldehyde	ASTM D6007	Carb II Compliant
Heavy Metals Content	ASTM F963	Pass
Indoor Sound Transmission IIC	ASTM E492/E989	66
Sound Transmission Class	ASTM E90/E413	68

For warranties, certifications, Installation and maintenance instructions please contact your SPEC Living sales representative or visit our website www.specliving.com



CONTACT

445 Hamilton Avenue
White Plains, NY 10601
MAIN 914.220.8195
SALES 914.220.8195
info@specliving.com