



SPECIFICATION SUMMARY

SPECWOOD Collection

SPEC Living
Multi Family Flooring Experts

PRODUCT

Thickness:	12mm (10mm Core + 2mm Sound Isolation Layer)
Width:	7.7"
Length:	60"
Packing:	19.08 SF Carton, 60 Cartons Pallet, 20 Pallets Per 40'
Underlayment:	2mm HD Eiso™ Sound Isolation Layer
Edge:	U Groove / Square Edge
Wear Layer:	45 gram Spectanium™ Embedded Finish Technology
Embossing:	EIR
Locking System:	Uniclic
Core:	Triton WP-501 (500+ Hour Waterproof)
Installation Grade:	Above, On, Below
Warranty:	Lifetime residential / Lifetime Structural / 10 Year Light Commercial

Tests:	Formaldehyde:	ASTM D6007-14	Result = Carb II & TSCA Title VI Compliant
	Critical radiant Flux:	ASTM E648-19a	Result = Meets or exceeds class I
	Dimensional Stability:	ASTM F2199-18	Result = Pass
	Coefficient of Friction:	ASTM D2394-2017	Result = MD Sliding Mean 0.41 Dry / 0.57 Wet
	Large Ball Impact Resistance:	NALFA 3.5	Result = Class 4 Heavy Commercial
	Small Ball Impact Resistance:	NALFA 3.6	Result = Class 4 Heavy Commercial
	Locking Strength:	ISO 24334-2014	Result = Pass Fmax(N) LSJ 1403 / SSI 1043
	Scratch Resistance:	ISO 1518-1-2019	Result = Pass Horizontal & Vertical @ 20(N)
	Thickness Swell:	NALFA 3.2	Result = Class 4 Heavy Commercial
	Wear Resistance:	NALFA 3.7	Result = Class 3+ Commercial
	Stain Resistance:	NALFA 3.4	Result = Class 4 Heavy Commercial
	Light Resistance:	NALFA 3.3	Result = Class 4 Heavy Commercial
	Castor Chair:	NALFA 3.9	Result = Class 4 35,000 Cycles No Effect
Surface Bonding:	NALFA 3.10	Result = Class 4 1.5 N/mm2	

Certifications:



For warranties, certifications, installation and maintenance instructions please contact your SPEC Living sales representative or visit our website www.specliving.com



CONTACT 445 Hamilton Avenue
White Plains, NY 10601
MAIN 914.220.8195
SALES 914.220.8195
info@specliving.com